

Fujitsu recommends Windows® 7.

Data Sheet

Fujitsu ESPRIMO P2560 Desktop PC

Your Immediately Available Office PC

The Fujitsu ESPRIMO P2560 is designed for price-conscious customers and is equipped with standard Intel® technology. This system meets every office requirement - especially those typical for small and medium-sized businesses. Fujitsu ESPRIMO P2560 is available from your dealer at all times and therefore an ideal choice once the decision to purchase has been taken.

Attractive price

PC for the day-to-day challenges of office life

- Proven Intel® technology

Designed and engineered in Germany

Outstanding quality and stable functions based on German production standards

- The development, production and function tests are all under one roof in Germany

Immediate availability

Short waiting times once purchase decision has been taken.

- Preferred versions available on-site



Components

Operating systems

Operating system	Windows® 7 Starter (EM) 32-bit Windows® 7 Home Basic (EM) 32-bit Windows® 7 Home Premium 64-bit Windows® 7 Professional 32-bit Windows® 7 Professional 64-bit
Operating system compatible	openSUSE Linux Windows Vista® Windows® XP
Operating system notes	Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via http://support.ts.fujitsu.com

Base unit	ESPRIMO P2560
-----------	---------------

Mainboard

Mainboard type	D3041
Formfactor	reduced µATX
Chipset	Intel® G41
Processor socket	LGA 775
Processor quantity maximum	1
System bus (FSB / HT / QPI)	up to 1333 MHz
Memory slots	2 DIMM (DDR3)
Supported capacity RAM (max.)	8 GB
Memory frequency	1066 MHz
Memory notes	For combinations of 32-bit operating systems with 3 GB of memory or above the accessible memory may be reduced to 3 GB or less (depending on system configuration). Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same
LAN	10/100/1000 MBit/s Realtek RTL8111DL
BIOS version	Phoenix 6.0
BIOS features	BIOS based on Phoenix SecureCore Recovery BIOS
Audio codec	Realtek ALC663
Audio features	High Definition audio, 5.1 surround sound

I/O controller on board

Serial ATA total	4
Controller functions	Serial ATA II 3 GBit

Interfaces

Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	8
USB front	2
USB rear	4
USB internal	2
VGA	1
DisplayPort	1 (optional)

Interfaces

DVI	1 (optional)
Serial (RS-232)	1 (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
Interface Module notes	Anytime USB charge functionality

Input device / components

Optical USB wheel mouse
Keyboard

Drive bays

Drive bays total	5
3.5-inch internal bays	2
3.5-inch external bays	1
5.25-inch external bays	2

Slots

PCI-Express x16	1 x (210 mm /) Full height
PCI-Express x1	1 x (/) Full height
PCI (32-bit / 33 MHz)	2 x (170/ 220 mm /) Full height

Graphics on board

Graphics brand name	Intel® GMA 4500
Shared video memory	up to 1759 MB

Refresh rate 1024 x 768 (recommended / max.) 85 Hz / -

Refresh rate 1280 x 1024 (recommended / max.) 85 Hz / -

Refresh rate 1600 x 1200 (recommended / max.) 85 Hz / -

TFT resolution (VGA)
1360 x 768 pixel
1440 x 900 pixel
1600 x 900 pixel
1680 x 1050 pixel
1920 x 1080 pixel
1920 x 1200 pixel

Graphics features
DirectX 10
HDCP support
OpenGL® 2.0

Graphics notes
Tested resolutions, depending on display type additional resolutions and frequencies possible
Shared memory depending on main memory size
Resolution (color depth up to 32 Bit/pixel)
For TFT we recommend using 60Hz

Electrical values

	0-Watt mode with hard-off switch
Power supply input	200 - 240 V ~1,5A
Rated voltage range	200 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	200 V - 240 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	300 W
Monitor outlet	No

Power consumption

Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=2a51d0d3-000c-47a3-ae8a-19c00547e984

Heat dissipation

Heat dissipation notes	See white paper Energy Consumption
------------------------	------------------------------------

Noise for standard configuration (HDD, ODD, FDD)

Noise emission	According to ISO9296
----------------	----------------------

Related Processors for noise	Intel® Core™2 Quad Q8300
------------------------------	--------------------------

Noise Operation mode 1: ODD load (Blue angel requirement)	5.1 B / 36 dB(A)
--	------------------

Noise Operation mode 2: HDD load (Blue angel requirement)	4.5 B / 30 dB(A)
--	------------------

Noise Operation mode 3: CPU 90% load (Blue angel requirement)	5.1 B / 36 dB(A)
--	------------------

Noise Operation mode 4: High load	5.2 B / 37 dB(A)
-----------------------------------	------------------

Noise Operation mode 5: Office	4.7 B / 32 dB(A)
--------------------------------	------------------

applications

Idle mode (Blue Angel requirement)	4.4 B / 29 dB(A)
------------------------------------	------------------

Noise notes / description	A weighted sound power level L _{wad} (in B) / workplace related A-weighted sound pressure level L _{pAm} (in dB(A)), Bystander position
---------------------------	---

Dimensions / Weight / Environmental

Dimensions (W x D x H)	175 x 425 x 353 mm
------------------------	--------------------

6.89 x 16.74 x 13.9 inch

Operating position	Vertical
--------------------	----------

Weight	approx. 11 kg
--------	---------------

Weight (lbs)	24.25 lbs
--------------	-----------

Weight notes	Actual weight may vary depending on configuration
--------------	---

Operating ambient temperature	15 - 35°C
-------------------------------	-----------

Compliance

Product	ESPRIMO P2560
---------	---------------

Model	MI4W-D3041
-------	------------

Europe	CE
--------	----

Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL)
--------	--

Compliance link	https://sp.ts.fujitsu.com/sites/certificates/
-----------------	---

Additional Software

Additional software (preinstalled)	Nero Essentials S (burning software) Norton Internet Security (incl. Firewall) 60 days version
------------------------------------	---

Additional software (optional)	Drivers & Utilities DVD (DUDVD) Recovery DVD for Windows® Nero 9 Essentials XL
--------------------------------	--

Compatibility (references)

DMI 2.0

PC 2001

WMI 1.5

USB 2.0

SMBIOS

Manageability

Manageability technology	DeskUpdate Driver management
--------------------------	------------------------------

PXE 2.1 Boot code

Wake up from S5 (off mode)

DeskView components	WoL (Wake on LAN)
---------------------	-------------------

Security

System protection	Kensington Lock support
-------------------	-------------------------

Eye for padlock

Security

Audit proof protection	Boot sector virus protection Control of external interfaces
Access protection	User and supervisor BIOS password Optional: Access protection via external SmartCard reader

Packaging information

Packaging dimension (mm)	500 x 290 x 540 mm
Packaging dimension (inch)	19.69 x 11.42 x 21.26 inch
Max. quantity / pallet	24
Material - Weight (g) Carton	1270 g
Material - Weight (lbs) Carton	2.8 lbs
Material - Weight (g) EPS / PS	210 g
Material - Weight (lbs) EPS / PS	0.46 lbs
Material - Weight (g) PE	60 g
Material - Weight (lbs) PE	0.13 lbs
Packaging notes	printed user documentation is bleached in chlorine free process

Warranty

Service level	(depending on country)
Maintenance and Support Services - the perfect extension	
Recommended Service	5x9, Response Time: Next Business Day
Spare Parts availability	3 years
Service Weblink	http://www.fujitsu.com/fts/services/support/index.html

More information

Fujitsu platform solutions

In addition to Fujitsu ESPRIMO P2560, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ESPRIMO P2560, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions
Website: www.fujitsu.com/fts
2012-05-31 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions